



Technology that connects



Handheld screwdriver  
with automatic feed system  
LTP & ETP

# Handheld screwdriver with automatic feed system LTP & ETP



## Technical data for LTP:

Drive:	Compressed air motor with push start
Torque range:	2 – 7 Nm
Speed:	max. 2000 RPM
Head diameter:	3 – 15 mm
Weight:	1.5 – 1.9 kg
Total length:	approx. 370 mm
Automatic screw feed system:	Weber feed and control units

## Technical data for ETP:

Drive:	EC servo motor with electrical release
Torque range:	0.4 – 7 Nm
Speed:	1 – 2000 RPM
Head diameter:	3 – 15 mm
Weight:	1.5 – 1.9 kg
Total length:	approx. 390 mm
Automatic screw feed system:	Weber feed and control units

## Features:

- Handheld screwdriving system can be easily and economically converted to a stationary screwdriving system
- Compact design
- High axial forces of the screwdriver are possible
- High-quality standard components
- Torque-based shut-off or depth based shut-off (adjustable)

## Weber Schraubautomaten GmbH

Hans-Urmiller-Ring 56  
82515 Wolfratshausen  
Germany  
Tel.: +49 (8171) 406-0  
Fax: +49 (8171) 406-111  
[info@weber-online.com](mailto:info@weber-online.com)  
[www.weber-online.com](http://www.weber-online.com)